



SPIKE Midi

SPIKE Midi LED light combines aesthetics with LED advanced lighting technology. This distinctive model is compact and available in different beam angles there by offering lighting designers and architects innovative ways to light landscapes.


The unique design ensures high quality lighting even in harsh environmental conditions.
Available in 3W and 9W versions.



SPECIFICATIONS

WATTAGE	3W, 9W
NUMBER OF LED'S	3
DIMENSIONS	3.55 in. (90mm) dia x 13.4 in. (340mm) H
WEIGHT	1 kg
COLOR TEMPERATURE	3000K (Warm White), 5500K (Cool White)
LINE VOLTAGE	100 - 240V AC
POWER SUPPLY	Integral
DIMMABILITY	Non-Dimmable
DIFFUSER	Heat resistant glass
BODY MATERIAL	Body-Aluminium, Spike-Aluminium
EXTERIOR COLOR	White, Black, Silver, Brushed Aluminium
ENVIRONMENTAL RATINGS	IP65
OPERATING TEMPERATURE	-10°C to +45°C
CERTIFICATIONS	RoHS, CE

DIMENSIONS



PRODUCT SELECTION GUIDE

PRODUCT	COLOR TEMP	WATTS	BEAM ANGLES (DEGREES)	COLOR
GLL-SPIKE MIDI	WW-Warm White 3000K	3W	25	W-White B-Black S-Silver A-Brushed Aluminium
	CW-Cool White 5500K	9W	28	

Example: GLL-SPIKE MIDI-CW-9W-25-W

APPLICATIONS

Lighting of plants, trees, shrubs, hedges, lawns and structures.

